





# TECHNIQUE FOR PEOPLE



erkules has designed and manufactured "technique for people" since 1974. In close co-operation with users "on site", we create workshop equipment which is economically smart with and through its ergonomics.

Superior technique setting standards: Lifts for paint- and bodyshops, automatic spray gun cleaners, dust extraction units.

These are all examples for products which have become state of art for modern, future-orientated workshops.

he Herkules concept "technique for people" has been successfully incorporated.

The products are worldwide highly acknowledged and distributed.



A selection of people and brands relying on us:
Akzo Coatings · Audi · BMW
Deutsche Bahn AG · Ford · Glasurit
Nexa Autocolor · Lufthansa
Volkswagen · Opel · Daimler AG
DuPont · Axalta · Porsche · Standox
Spies Hecker



By means of the newest tools and machines, Herkules produces and manufactures high quality paint- and bodyshop products at our headquarters in Kassel. Thanks to numerous user experiences, innovative technology and well-planned concepts, Herkules is able to make the products suit the high demands on the market.

The quality of our products - expressed through a 3 year guarantee on all lifts - is ensured during the entire production in Kassel. The lifts and the dust extractions are all 100 % made in Germany.

We would like to invite you to our exhibition and training centre in Kassel, where you can see and test all of our products.

Welcome!



erkules is delighted to present some new products to you in this catalogue. They are all of the finest Herkules-quality, and loyal to our concept "technique for people" - this is not only our corporate philosophy, but also a promise to our customers.

# Products:







## Lifts I Paint- and Bodyshop


Lifts HLS	6
Lift HLS-1200 For paint- and bodyshops	7
Lift HLS-1600 The professional lift with a working height of 1600 mm	8
HLS-3200 The lift with 3.2 to loading capacity	9
Lifts HLS-Duo	10
Lift HLS-1200 Duo Two lift systems perfect combined	11
<b>HLS-3200 Duo</b> The double system lifting platform with increased lifting power	12
Cross beam For the free-lift of large vehicles	13
JACK 3 to The mobile jack for the flexible stroke of the soil	<b>13</b>
Lift HLS-1600 U Comfortable work on the top of the car	14
Lift HLQ For spraybooths with sideways transportation on roller trolley	<b>15</b>
Painter-Lift The working lift for the painter	16
<b>Transmobil</b> The workshop transportation system	18

## Lifts II Workshop and Tyre service

Herkules-lift mobil The lift for the bodyshop	20
Herkules-lift RS Tyre service lift	22
Herkules-lift RS 3 to Tyre service lift	23
Lift K 700 Maintenance lift for the workshop	24
Lifts - a comparison (Overview)	26







Cleaning	27	The spray gun cleaning system	Cleanpoint
	NEW 31	t Duo-MAX The multi-purpose device	Cleanpoint
	32	ion	Drain stati
	33	Aqua-Rinse Spray gun cleaner	Herkules A
Dust Extraction	34	Central dust extraction system	Hexadust (
	NEW 36	<b>Turbo</b> (Wall mounted solution)	Hexacomb
	NEW 1 37	<b>Turbo</b> (Cabinet model)	Hexacomb
	38	<b>Turbo</b> Dust extraction for self-installation	Hexacomb
	NEW 1 39		T-2 mobile
	40		Hoses
Workshop	41	ler	Lacky Tend
	NEW 41	nper	Lacky Bum
	42	e	Lacky table
	42	d	Paint stand
	43	er	Paper bale
	43	h	Step-bench
	44	your contact	Herkules -



### The perfect lift for preparation and finish



he approved lifts HLS are available in three types for different demands.

### All of them have:

- Stepless lifting heights
- Due to low construction height easy to drive on
- Simple access to interim drive over ramps and deviate loading ramps
- ATEX option with pneumatic lifting technology
- 3 years lift warranty



The easy installation facilitates an individual planning of body shops by using the existing space optimally.



Flush mounted with low pit depth.









Quality is increased by ergonomic work in an uncramped posture.



The lift HLS as in-ground installation in the spray booth.

# HLS 1200



The perfect lift for paint and body-shops

l Vearly 85 % of all car damages require the worker to work in a stooped position. This causes fatigue and can also lead to long-term health problems. With the special paint-lift, the HFRKULES work can be done in an ergonomically correct upright position. The work efficiency is increased and the quality is improved by better visual control opportunities.

### 

### on-ground

Simply fix with screws and dowels, and the lift is ready for immediate use. Item No.: HLS1200-11





### haamaan waa dh

### flush mounted

Flush mounted to concrete or grids.

Item No.: HLS1200-14



Lifting height



### 

### rail transport

Lift for rail transport

Item No.: HLS1200-13






### **Technical data:**

Loading Capacity	2.5	ιΟ
Weight	700	kg
Air supply	8	bar
HLS 1200-11		
Working height	~1100	mm
Object height only	110	mm
Lifting height	930	mm

HLS 1200-14
Working height ~1000 mm
Pit depth 115 mm
Lifting height 930 mm

HLS 1200-13
Working height ~1100 mm
Object height only 135 mm

930 mm





The paint- and bodyshop lift with increased lifting height



Advantage of the lifts: The ergonomic work and the good visual control opportunities increase the efficiency and ensure the health of the employees.

The intelligent construction with the innovative extras and the extended lifting height makes the HLS-1600 the perfect professional lift for the future-oriented paintshops. Thanks to its compact construction, the lift is also suited for smaller workshops. Due to its fold down driving tracks and a drive-on ramp which is level with the rest of the lift, working with the HLS-1600 is easier than working with many other lift types.



### 

## on-ground

Ready for immediate use. Easily accessible due to the ramps.

.6

Item No.: HLS1600-11

# 3 to



The new HLS-1600 has both: a new compact construction method and an extended lifting height which is superior to traditional lifts.


### 

### flush mounted

Flush mounted to concrete or grids. Ideal for new installation sites.

Item No.: HLS1600-14





### **Technical data:**

Loading capacity Weight Air supply	3 800 8	to kg bar
HLS 1600-11 Working height Object height only Lifting height	~1600 160 1300	mm mm mm
HLS 1600-14 Working height Pit depth Lifting height	~1400 160 1150	mm mm mm

# HLS 3200

TECHNIK FÜR MENSCHEN

The lift with 3.2 to loading capacity



he HLS 3200 is with a loading capacity of 3.2 to constructed for heavy vehicles. This creates a safe work and provides the possibility also for SUVs and small vans.

The extended platform allows the lifting also for extended vehicles. The smooth lifting increases the access to damaged areas and the ergonomic work process.





### 

### on-ground

Ready to use immediately. With ramps easily accessible.

Item No.: HLS 3200-11







buildings.


flush mounted

Item No.: HLS3200-14



Optimal flush mounted installation.

It is particularly advantageous for new



#### **Technical data:**

Loading capacity 3.2 to Weight 750 kg
Air supply 8 bar

HLS 3200-11

Working height ~1050 mm Object height only 122 mm Lifting height variable to strain

HLS 3200-14

Working height ~950 mm
Pit depth 130 mm
Lifting height variable to strain

# Lifts HLS Duo



Two lift systems perfect combined

### One lift - two possibilities:



for the on-ground version. Lifted on the wheels Wheel free lift

he approved HLS lifts are available in three types for different demands.

### All of them have:

- Stepless lifting heights
- With ramps easily to drive-on
- Simple access to interim drive over ramp and deviate loading ramps
- ATEX option with pneumatic lifting technology
- 3 years lift warranty





The deviate loading ramps make the access to the panel so easy.



\*The shown fold down supports are only

The stepless lifting height secures the ergonomic work process in the upper position.









Easy positioning of the lifting points also of extremely flat vehicles.



Loading ramps secure against fall down.

# HLS 1200 Duo



The lift system with double operation

The workshop lifts for almost all standards. The lifting of the car could be either on wheels or for wheel free work

Uncramped posture and better visibility improve quality thanks to different working heights that can be changed smoothly.

Due to its fold down driving tracks and ramps which is level with the rest of the lift, working is easier.



#### on-ground

Item No.: HLS1200-Duo-11





#### . Barananan wasan baran

#### flush mounted

Optimal flush mounted installation. It is particularly advantageous for new buildings.

Item No.: HLS1200-DUO-14





### **Technical data:**

Loading capacity	2.5	to
Weight	850	kg
Air supply	8	bar

HLS 1200-DUO-11

Working height ~1100 mm Object height only 110 mm Construction height


with arms 155 mm Lifting height max. 930 mm

HLS 1200-DUO-14

Working height ~1000 mm
Pit depth 115 mm
Lifting height max. 825 mm







# HLS 3200 Duo



The double system lifting platform with increased lifting power

With 3.2 to loading capacity and the extended platform size the HLS Duo 3200 is also made for heavy vehicles and small vans.

Thanks to the extractable ramps (only on-ground version) a safe lifting from small to large vehicles is always attainable.

With the double functionality as standard lift as well as wheel free lift a multifunction workplace is realized.



### on-ground

Item No.: HLS3200-Duo-11





### flush mounted

Item No.: HLS3200-DUO-14





### **Technical data:**

Loading capacity	3.2	to
Weight	850	kg
Air supply	8	bar

HLS 3200-DUO-11 Working height ~1050 mm Object height only 120 mm

Construction height
with arms 170 mm
Lifting height variable

to strain
HLS 3200-DUO-14


Working height ~950 mm
Pit depth 130 mm
Lifting height variable to strain



The cross beam (look page 13) is the applied solution, where the lifting points of the swivel arms are exceeded.

The drive on ramps are adjustable in four catches (on-ground version only). For this reason the lift can be adapted to the required wheel base.

Supported area of the swivel arms in mm



# Cross beam



The safe free-lift for large vehicles

For the wheel free-lift of large vehicles the cross beam is the applied solution, where the lifting points of the swivel arms are exceeded.


The cross beam will be placed on top of the swivel arms and is an option for the HLS 3200 DUO and the RS 3 to.







Item No.: 300-375





# JACK 3 to

The mobile workshop jack. Can easily and securely be used on the workshop floor.

- Really flat just 120 mm
- Super lifting height 410 mm
- Really light just 8 kg
- Really strong 3.0 to loading capacity





Item No.: 300-246

### **Technical data:**

Loading capacity 3 to
Height max. 410 mm
Height min. 120 mm
Weight 8 kg
Air supply 8 bar





The immersible lift for a comfortable work on the top of the car

he HLS 1600-U allows the lowering of the car in the booth ground for easy work in the roof area.

This increases the productivity and the safety of the lift.

- Regular lifting for an ergonomic work at the vehicle
- Comfortable work on the top of the vehicle thanks to the immersion of the lift into the gratings of the booth or into the body shop without ladders or other insecure tools
- Smooth lifting and lowering to desired working height
- Perfect for SUVs (sport utility vehicle) and Vans

Item No.: HLS1600-15











## **Technical data:**

Loading capacity 3.0 Length of the platform 4030 mm Width of the platform 1985 mm Depth of the pit 475 mm Weight 920 kg Air supply 8 bar




Optimal approach to the vehicle and to the top of the vehicle.



The HLS1600-U lifted for the work on the lower part of the vehicle.

Working height ~ 850 mm



The HLS1600-U on the bottom for an easy access.



The HLS1600-U immersed for the work on the upper parts of the vehicle.

Recessed depth up to 300 mm

# Herkules HLQ

TECHNIK #ENSCHEN

**Drive-over lift with trolleys for side transportation** 



For spraybooths equipped with trolleys for side transportation. Safe vehicle lifting on its wheels. The side transport with trolleys ensures the quality and improves the performance.



The vehicle will be lifted up at the trolleys. During the lowering the stool guide rolls catch back to the rail.



Fatigue-proof and better visibility for your work. The spray gun is easier to manage also at the underpart.



You can move the vehicle to the dryer booth easily. The lift is ready for the next job.






### **Technical data:**

Loading capacity 2.5 to Weight 500 kg
Air supply 8 bar Working height ~ 800 mm
The flush-mounted lift is prepared for the installation into grids with adjustment to the existing rails.

Item No.: HLQ-01








## **Painter**




The working lift for the painter

he new development for the state-of-the-art paint shop.

Safe lifting for all works around the



• For prep area and spray booth







#### Painter 01

Working height up to 3.25 m Platform dimensions 2000 x 700 mm Loading capacity 150 kg Item No.: Painter-01





#### Painter 02

Working height up to 4 m Platform dimensions 3500 x 700 mm Loading capacity 150 kg Item No.: Painter-02

### Painter 04

Working height up to 4 m Platform dimensions 2000 x 700 mm Loading capacity 150 kg Item No.: Painter-04





### Painter 05


Working height up to 4 m Platform dimensions 3500 x 700 mm Loading capacity 250 kg Item No.: Painter-05

Air supply

8 bar







Painter secures safe standing and ergonomic working position for painter when working at higher vehicles.




The painter is easily moveable with the wheels. Both at prep work and spray booths – excellent for small spaces.






On the platform are several air supplies as well as storage space for the tools. Therefore they are always within reach.









# Transmobile



### Rail-free handling and transportation system



- Reduces vehicle transportation
- · Can easily and safely be operated by only one person
- Makes the most of your space thanks to its tight entry angle
- Powerful self-drive with no harmful exhaust gases
- Covered vehicle surfaces remain undamaged
- · Final cleaning of vehicle interior is no longer necessary
- Our product makes your work easier and increases the work quality

he revolutionary system for modern paintshops. Thanks to a quicker and safer work routine, the Transmobile creates new capacity.

The Transmobile drastically reduces the work involved in vehicle transportation around the shop. Your benefit is an even better used time for new jobs.

The transportation system consists of the remote controlled automotive transmobile, and the lift HLS and HLS

Can be used in any shop with a level surface - even in the spraybooth with grid floor.

The use of the Transmobile pays off: better workshop utilisation, lower wage costs and a great amount of time saved.

### **Transmobile**

2.5 to Version Item No.: HLT-03 3.2 to Version Item No.: HLT-04

### **Technical data:**

Loading capacity 2.5/3.2 to Weight 560/600 kg Drive















# Transmobile







The cars are on lifts from the moment the work is started right through to the final inspections. It can safely and quickly be moved to subsequent workstations.



Can be used in any shop with a level floor - even in the spraybooth with grid floor.



The lfits for Transmobile are made for use with moving transport – easy to use.



Moving the vehicles through tight spaces is easy and safe.





# Herkules-lift mobile



The new lift for bodyshops



# Herkules-lift mobile

The lift is ready for immediate use no installation necessary! With an additional set of wheels it is mobile in the shop.

## 

#### on-ground

Ready for immediate use. Item No.: HM1100-01





Fast lifting
Ergonomic lifting height
Various possibilities of use
Small space requirements
No installation required
Operated solely by air pressure

flush mounted
Optimal in-ground installation.
Item No.: HM1100-04



# Herkules-lift mobile








Flush-mounted installation in a spray booth.



The swivel arms easily reach the vehicles' original lifting points.
All swivel arms are moveable horizontally at the lift.



The lifting dishes negotiate a distance of 140 mm height and they are moveable at the swivel arm.



The radius of the swivel arms allows also the safe fixing of wide vehicles.

Supported area of the swivel arms in mm

#### **Technical data:**


Loading capacity 2.8 to Weight 510 kg
Air supply 8 bar


Item No.: HM 1100-01


Working height ~1100 mm Object height 115 mm Lifting height 930 mm

Item No.: HM 1100-04

Working height ~1000 mm
Pit depth 115 mm
Lifting height 825 mm









Fast tyre- and brake-service



# Tyre service lift Herkules-lift RS

Due to the low construction height, the easy positioning of the blocks through outside markings and the high lifting speed, the lift enables you to service more vehicles in a short time. This increases the productivity of your shop, especially in the high seasons.

- 2.5 to lifting capacity
- No installation required
- Ready for immediate use
- Operated solely by air pressure
- Mobile with handle and wheels (optional)

Item No.: RS570-01








Safe lifting every time thanks to the easy fixing of original lifting points. If ramps are removed, short wheel based cars can also be serviced.



The lift is equipped with telescoping arms, and therefore it is also suitable for small vans and cars with long wheel distance.



#### **Technical data:**

Loading capacity	2.5	to
Weight	520	kg
Air supply	8	bar
Working height	~500	mm
Object height only	72	mm
Lifting height	428	mm

# Herkules-lift RS 3 to





Due to the increased lifting capacity and the big lift plate, fast tyre fitting is not a problem even for large vehicles. Due to the low construction height and the fast lifting speed, the Herkules-lift RS 3 enables you to service more vehicles in a short time. This increases the productivity of your shop especially in peak seasons.

The lift is ready for immediate usecompressed air supply and a level floor is all you require.

Item No.: RS-3T-01






## Technical data:

Loading capacity	3	to
Weight	550	kg
Air supply	8	bar
Working height	~500	mm
Object height only	77	mm
Lifting height	423	mm

- · Loading capacity 3 to
- Non-damaging access due to a low drive-over height
- Swivel arms easily reach the vehicles' original lifting points
- Smooth pneumatic lifting up to 500 mm
- No damage to vehicle wheels due to rounded-off angles of the swivel arms
- Side foot protection plates guard the operator
- No installation required Immediate use without installation



With the cross beam (page 13) the lifting points of large vehicles are ensured.



# Herkules-lift K 700



Increased lifting height - more possibilities



- Loading capacity 2.8 to
- Non-damaging access due to a low drive-over height
- Swivel arms easily reach the vehicles' original lifting points
- Smooth pneumatic lifting up to 930 mm
- Ergonomic work in upright position
- No damage to vehicle wheels due to rounded-off angles of the swivel arms
- No installation required Immediate use without installation

# Tyre Service Lift K700

The K700 is an universally applicable lift for tyre service workshops. The lifting height of 930 mm allows an ergonomic work at a height of approx. 1100 mm for all work to be accomplished at the tyre service, brake-service or tuning operations.

With a loading capacity of 2.8 to the K700 is also suitable for work on heavy Limousines and SUV's.






Item No.: K700-45

### **Technical data:**

Loading capacity Weight	2.8 720	to kg
Air supply	8	bar
Working height	~1100	mm
Object height only	110	mm
Lifting height	930	mm

2010 mm 930 mm 2250 mm











The double-wedge ramp allows an easy and non-damaging access even with lowered vehicles.





	HLS 1200-11	HLS 1200-14	HLS 1600-11	HLS 1600-14	HLS 3200-11	HLS 3200-14	HLS 1200-Duo-11	HLS 1200-Duo-14	HLS 3200-Duo-11	HLS 3200-Duo-14	HLS 1600-15	HLQ-01	HM 1100-01	HM 1100-04	RS 570-01	RS 3t-01	K 700-45
Scope of duties																	
Paint- and body work		•	•	•	•	•	•	•	•	•	•	•	•	•			
Tyrework							•	•		•			•	•	•	•	
<b>Driving specifications</b>																	
Over ramps 4 pieces		•		•		•		•		•	•						
Over ramps 2 pieces	•		•		•		•										
Drive through possibility	()	•	()	•	()	•	()	•	()	•	•	•	•	•	•	•	
Lifting specifications																	
Chassis supported							•	•		•			•	•	•	•	()
Wheel supported	•	•	•	•	•	•	•	•		•	•	•					
Technical specifications																	
Lifting Capacity in to	2.5	2.5	3	3	3.2	3.2	2.5	2.5	3.2	3.2	3	2.5	2.8	2.8	2.8	3	2.8
Object height in cm	11	11	15	11	12	12	11	11	12	12	16	10	11	11	7	8	11
Working height in cm	110	100	160	145	max. 105	max. 95	110	100	max. 105	max. 95	115	80	110	110	70	70	110
Net lifting height in cm	82	82	115	115	max. 77	max. 77	82	82	max. 77	max. 77	115	64	82	82	50	50	82
Air supply								- ma	x. 8 ł	oar							
Installation specifications																	
Flush Mounted		•		•		•		•		•	•	•					
On Ground			•		•		•						•		•	•	
Mobile													()				
Rail												•					

Standard optional ()

# Cleanpoint



The superior cleaning system for the painter




Spray gun cleaning machines at the highest level:

**Cleanpoint** 

The innovation.

The patended magnetic gun holder fixates a spray gun in a position where the gun's air channels are protected. The air channel is free connected to the solvent entering, so there is no longer the risk of solvent entering the air channels.















- Improved cleaning performance and more features.
- Magnetic gun holder fixates the gun in an optimal washing position.
- Simultaneous manual and automatic cleaning of up to 4 guns.
- Convenient handling due to **ergonomic design**.
- Persuasive design in quality stainless steel.
- For solvents as well as water.








Attractive design and impressive functionality. The magnetic holder for the spray gun can be individually placed whether inside or outside of the unit.









The innovative washing room for the automatic wash process: The Auto-Box. The powerful wash pumps and the high efficiency of the nozzles make the washing result more efficient consuming less solvent.



Another major innovation is the magnetic gun holder. The new magnetic gun holder pulls the trigger to open the paint channel and fixates a gun in seconds, in one simple step. It fixates the gun in a position where the gun's air channels are protected, facing downwards, so there is no risk of solvent entering the air channels. Through clever design, there is no longer any need for separate extension tubes, trigger clips, air purge lines etc.

All commercial containers (60 liters) can be easily ranked in the trolley. Each trolley is designed with a tray as overflow protection.

# Cleanpoint



#### **CP-Quattro**

The perfect solution for solvent. With two automatic washing rooms and two basins for the manual cleaning. Up to four guns can cleaned simultaneous. The controlling for automatic and manual cleaning will operated with foot pedals.

For solvents Item No.: CP-QUATTRO



## **Technical data:**

Subject to technical changes.

Height 1510 mm
Width 1185 mm
Depth 650 mm
Weight 95 kg
Compressed air supply 7-12 bar
Air consumption 150 l/min
Exhaust power 800 m³/h

#### CP-Duo

All components for automatic and manual cleaning in one unit.

The powerful wash pumps and the high efficiency of the nozzles make the washing result more efficient consuming less solvent.

For solvents Item No.: CP-DUO



## Technical data:

Height 1510 mm
Width 835 mm
Depth 650 mm
Weight 75 kg
Compressed air supply 7-12 bar
Air consumption 150 l/min
Exhaust power 500 m³/h

Subject to technical changes.



#### **CP-Uno**

Compact station for manual cleaning with a brush and a spray nozzle. Like all other units the CP-UNO is equipped with brush for re-circulating solvent and a spray gun for fresh solvent as well as a blowout pistol.

For solvents Item No.: CP-UNO

#### **Technical data:**

Height 1510 mm
Width 835 mm
Depth 650 mm
Weight 70 kg
Compressed air supply 7-12 bar
Air consumption 150 l/min
Exhaust power 500 m³/h

Subject to technical changes.



### CP-Duo-Aqua

All components for automatic and manual cleaning in one unit. For water and water boned solvent (for example AquaSolve). The CP-Duo-Aqua has the Auto-Box for automatic cleaning and a basin for manual cleaning.



## **Technical data:**

Height 1510 mm
Width 835 mm
Depth 650 mm
Weight 65 kg
Compressed air supply 7-12 bar
Air consumption 250 l/min
Exhaust power 500 m³/h

Subject to technical changes.



# AquaSolve

The new concentrate for the water-based gun cleaning.

- Makes cleaning quick and easy
- For automatic and manual cleaning
- Anti-corrosion additives and cleaners to protect the spray gun
- Disposal by coagulation remains
- Applicable for all color brands

Item No.: DH-230120

# Cleanpoint Duo-Max







### **Maximum functionality:**

Automatic and manual cleaning - plus ink residue disposal in one device

#### **Maximum usability:**

Easy control and access to all operation components

### **Maximum quality:**

Well-engineered, practice proved technology in elegant stainless steel

#### **CP-Duo-MAX**

The Cleanpoint CP-Duo-MAX has an automatic washing room, a basin for manual cleaning with a brush and a drainer for residual paints. Sideways is a foot pedal to control the brush cleaner and a flexibly place able blowgun. Inside you can place the container for fresh thinning, circulating cleaner and a waste canister for residual paint. Connection for a suction gun holder and drain tray completes this unit.

For solvents Item No.: CP-DUO-MAX






A knob manages the automatic cleaning.



The manual workstation is equipped with brush for re-circulating solvent and a spray gun for fresh solvent.



With the new drain tray, residual paint in spray guns or cups will be disposed.

#### Technical data:

Height 1510 mm
Width 1185 mm
Depth 650 mm
Weight 70 kg
Compressed air supply 7-12 bar
Air consumption 150 l/min
Exhaust power 500 m³/h

Subject to technical changes.









# Drain station



### To collect residue of lacquers

The Herkules **drain station** is the cost-saving add-on unit for automatic spray gun cleaning systems. Drained guns and cups go easy on the cleaning agent in the system. The increased service life saves a lot of resources.

- Thanks to the increased service life it saves solvents
- With blow-out channel for cleaning the gun interior
- Suitable for conventional and waterbased materials
- Clean workstation
- Optional extraction system is available as an accessory

Item No.: CP-TG01



The residues of lacquers are collected in a canister.
An optional exhaust avoids odour and healthrisks.



The residues of lacquers are collected in a canister. An optional exhaust avoids odour and healthrisks.



Spray guns and paint cups are simply placed in the drip openings.



Spray cups will just be placed above the drain opening.

### Technical data:

Height 1020 mm Width 400 mm Depth 500 mm



The **drain station** is the ideal add-on unit for all automatic spray gun cleaning systems. It drastically increases the service life of cleaning agents in the systems.

# Herkules Aqua-Rinse






The clean station for the quick colour change of water borne paint

he clean station is special designed for the disposable cup systems. The proper cleaning for spray guns is the result of spray out, rinsing and drying. All functions are integrated in one compact solution.

Leaving the spray booth to clean the spray gun is time consuming and inconvenient.


Proper cleaning means better quality





- Paint spray out funnel
- Paint channel rinse nozzle activates pump when pressed
- Air cap brush
- Air gun for drying the spray gun
- Diaphragm pump
- Clean water container

Item No.: DH-QR-10





Spray out the remaining paint



Rinse the paint channel



Wipe the air cap



Dry the gun



The modular designed dust extraction system

# Herkules Hexadust dust extraction system

Vacuum dust extraction solutions for workshops of any size. An individual analysis of your workshop setting will let us configure the ideal set up for your shop.

The Hexagon energy head or alternatively the multifunctional terminal will provide work places with vacuum power, air pressure and electricity. The standard automatic start and stop enables healthy working, a clean workshop and energy savings.





**Multifunctional terminal** Up to 2 sanders at the same time. 240 V Art.Nr. C1C-240

400 V Art.Nr. C1C-400

NEW !



**T 2 - Turbo**Up to 2 sanders at the same time.

Item No.: E1W



**T 2 - Turbo**Up to 2 sanders at the same time.

Item No.: E1S



**T 4 - Turbo**Up to 4 sanders at the same time.

Item No.: E1C




T 6 - Turbo Up to 8 sanders at the same time.

Item No.: E3K





The Hexadust dust extraction provides all working places in the workshop. The Hexagon energy head is compatible with all sanding tools.



Automatic system start for both air and electrical tools as well as an automatic pneumatic filter cleaning are standard equipment. With Hexadust dust extraction systems you have the choice between Hexagons with ceiling or wall assembly as well as swivel arm with a length of 5 m. The connection is a result of a pipe system.







# Hexacomb Turbo



A vacuum system for multiple users



# Hexacomb Turbo





Phone: +49 561 / 58 90 7-0 · Fax: +49 561 / 58 90 7-45 · www. herkules.de



The new Hexacomb combines recent product design, high efficiency and an user-friendly handling.

- Gallant design
- Adjustable compressed air connection
- Particularly silent
- Easy and safe removal of the dust bags



- ✓ Filling level indication through LED-signal
- Adjustable air pressure with manometer
- Real multiple user system: double connection for power supply, compressed air and extraction
- ✓ Powerful turbine
- ✓ Silent turbine due to optimized insulation





Safety guidance of the swivel arms through a smooth-running gear ring connection.



Ergonomic and dust-reduced dust disposal through a sliding plate and dust bag holders.



Dust-reduced disposal by opening the sliding plate. The dust goes into the dust bag.

## Very silent:

With a maximum of 64 dB more silent than a modern vacuum cleaner.

## Technical data:

Motor power 1300 W
Circulatory 220 m³/h
Depression 220 mbar
Filter area 10470 cm²
Noise level max. 64 dB
Electric tension 230 V
50-60 Hz

Jet fighter with a distance of 30 m	140
Pain threshold	130
Threshold of illness	120
Chain saw with a distance of 1 m	110
Disco with a distance of 1 m to the speakers	100
Diesel engine with a distance of 10 m	90
Border of a public highway 5 m	80
Vacuum cleaner with a distance of 1 m	70
Herkules Hexacomb Turbo	64
Normal speech with a distance of 1 m	60
Dishwasher	50
Quiet conversation	40
Hum of refrigerator	30
Rest noises in a television studio	20
Rustling of leaves in the distance	10

### New filter cleaning:

Filling level indication of the filter area through LED-signal. By opening the sliding piston the filters are cleaned automatically and the dust bag can be changed in a dust reduced way.

# T-2 Mobile



The mobile working place in the prep area

The new T-2 Mobile is a very flexible vacuum system for body shops.

The compact unit offers a huge storage surface and suspensions for tools and consumables.

With the big rollers the T-2 Mobile is moveable on grids and everywhere else in the workshop.

All required tools are immediately available.

Item No.: T2M





The powerful station supplies two working places with exhaust and energy.



The magnetic equipment holder can be freely positioned to all metal areas.



Very easy and almost dustless you can replace the dust from an ordinary bag.

- Strong vacuum power 1.3 kW/230 V
- Long life time
   (25.000 hours of operation)
- Automatic on/off for electronic and air-operated machines
- Automatic filter cleaning
- Silent turbine due to optimized insulation
- Dust-reduced disposal
- Compatible for all traditional sanding tools like Rupes, Hutchins, Festool, SIA, Mirka etc.









## no swivel-joint







Available hoses

 Vacuum hose
 F1A
 5 m

 F1B
 7 m

 F1C
 9 m

 Vacuum and compressed air
 F1D
 5 m
 F3D
 5 m

 F1E
 7 m
 F3E
 7 m

 F1F
 9 m
 F3F
 9 m

Vacuum with compressed air and grounding F1D-E 5 m F1E-E 7 m F1F-E 9 m

Vacuum and electricity F2D 5 m F2E 7 m F2F 9 m

Adaptor For Festool IAS 2 machines Item No.: 340-007

For Festool IAS 3 machines Item No.: 300-404

between turbine and hose or between hose and Hexagon





The carrying- and storage-system for the paint preparation and final assembly

With the "Lacky Tender" long ways to the storage are history.

Two stabilized basements in the lower area, a flexible grating ground and at any place with two small parts mountable box provides organization and clear view.

Prepared parts like doors, spoiler and wings can be stored in a safe way. The "Lacky Tender" increases your productivity considerable.

- Cushioned rack for bulks
- Safety fixation with tension belt
- Continuous extractable bearings
- Box, grating rack and grab handle can be individually positioned
- Clearly grid boxes and racks
- Easy shunting

Item No.: 300-297

The Tender provides beside the gratings and racks for bulks additionally capacity for working tools and consumables.




Safety shunting in the body shop.

### **Technical data:**

Length 900 mm Width 680 mm Height 2020 mm Weight 45 kg

Subject to technical changes.



# Lacky Bumper

The storage and transport rack for large parts

For safe storage and easy transportation of bulky vehicle parts.

- Adjustable in many ways
- Padded shelves
- Easy to rank

Art.Nr. 300-399



### Technical data:

Length 1200 mm Width 800 mm Height 2000 mm Weight 28 kg



# Lacky Table



### The preparation table for the paintshop


### **Herkules Lacky table**

This table is made of **stainless steel** and has a lot of storage space for painting materials and tools. Everything is at your hand, saving both time and effort.

The **lowered working surface** prevents solvent overflow. It has also got an **outflow tunnel** for pouring into a collecting tank. A **paper roll holder** is available as an accessory.



Thanks to the defined extraction at the bottom of the working surface, reliable extraction is possible. The solvent particles concentrated at the bottom are optimally drawn off through strong suction.





The extraction system can be connected to an already existing system. Herkules has a pneumatic extraction system available as an accessory.

#### **Technical data:**

Item No.: LT-05
Width 1200 mm
Item No.: LT-06
Width 1800 mm
Overall height 1395 mm
Depth 650 mm
Paper roll holder and extraction system available as accessories



## Paint stand



### **Herkules paint stand**

The quick and safe painting and assembly stand for paint- and bodyshops.

- Has a wide range of adjustments
- Robust but easy to handle
- Extendable

Item No.: BL-01





Provides space and reduces waste disposal charges

### Paper baler

**Up to 5 to pressing capacity** reduces volume drastically. Whether packing or masking - paper from the paintshop - the big front flap swallows it all! **Tied up easily in pressed state.** 

Achieves a 20 times more effective use of waste containers, and drastically reduces the waste disposal charges.


Thanks to the set of wheels with lockable casters a relocation is possible at any time.



Item No.: PAP-01



Capacity	5.0	to
Weight	250	kg
Air supply	8	bar
Flap opening:	415 x 680	mm
Bundle weight:	25 - 50	kg







Aluminium step-bench

For painting large vehicles

An essential "helping hand" when painting the roofs of larger vehicles such as vans and small trucks. When it is not in use it can easily be put away - it does not require a lot of space.

Item No.: 300-257

## Technical data:

Loading capacity 120 kg Weight 5.0 / 6.5 kg Dimensions 1000 x 330 x 325 mm 1190 x 330 x 600 mm



# V 15

**Subject to technical changes.** 



Headquarters & Production: Herkules Hebetechnik GmbH Falderbaumstr. 34 D-34123 Kassel Founded: 1974

Member of the Hedson Group



Phone: +49 561 / 5 89 07-0 · Fax: +49 561 / 5 89 07-45 · e-mail: info@herkules.de · Internet: www.herkules.de