



HIGH PRODUCTIVITY EASE OF USE LESS TECHNICIAN'S FATIGUE

monty® 8800 combines the high productivity features of a tabletop tyre changer and the high performances of those leverless.



POWERMONTTM

The innovative system to mount & demount tyres





smartSpeed[™] continuously controls the mount/ demount conditions in order to provide the optimum torque/speed combination to the motor

- SAFE: always the most appropriate torque to avoid interruption of the process and damages to tyre and rim
- FAST: automatically selects the maximum speed possible up to 20 rpm
- EASY TO USE: smartSpeed™ automatically sets the speed to the torque required



OPTIMUM BEAD BREAKER SYSTEM

The most performing solution for any tyre's types



Dynamic bead breaker

- The bead breaking of choice for RFT, UHP and low aspect ratio tires – Precise and damage free
- Disk position synchronized by servo drive –Fast & precise
- Disk pneumatic tilt Optimum performance with sticked beads
- Ergonomic & effortless



On floor bead breaker *

- The fastest solution for tyres with soft sidewall and high aspect ratio
- Ease of use
- Shovel actuated by a switch on the handle
- On floor bead breaker assures high productivity with standard tyres

(*) monty® 8800s and higher models

QUICKLOKTM

The fast and effortless automatic wheel clamping

- Electromechanical lock and unlock of the wheel via switch on the control panel for easy clamping
- Wireless command on the shaft's handle to operate wheel lock/unlock operations (monty[®] 8800g and monty[®] 8800p)
- Center post design more flexibility in wheel clamping
- No restriction on rim size
- No wheel damage
- No need to "push" the rim into the jaws
- No jaw protection
- Constant locking force
- Fast as a tabletop tyre changer with steel wheels
- Easy and damage free with UHP and run-flat tyres
- Effortless

POWERMONTTM

The innovative system to mount & demount tyres



FAST

- Automatic synchronization of all tools positions
- Fast disengage and repositioning of the mount/demount tool
- Standalone tool for lower bead mounting

SAFE

- Thin mount / demount finger protects the bead from stress during mounting
- Servo assisted movement of the mount /demount tool, the finger follows the rim profile and prevents damages of TPMS and valve
- Integral and soft tool protection avoids rim damage

EASY TO USE

• Control of the mount/demount tool's trajectory · Intuitive and simple control of the operations

RELIABLE

• Long lasting mount / demount tool made of steel with integrated plastic protection

Demounting sequence









Mounting sequence









Features	monty® 8800b	monty® 8800s	monty® 8800g	monty® 8800p
Clamping range	12" – 30"	12" – 30"	12" – 30"	12" – 30"
Max tyre width	380 mm	380 mm	380 mm	380 mm
Max wheel dimension	47"	47"	47"	47"
smartSpeed™	CW 7 – 20 rpm	CCW 7 – 20 rpm	CCW 7 – 20 rpm	CCW 7 – 20 rpm
quickLOK™	control panel	control panel	w/wireless command	w/wireless command
powerMONT™	standard	standard	standard	standard
Optimum bead breaker system	n.a	standard	standard	standard
Bottom bead viewer	mirror	mirror	mirror	camera
Bead seater	n.a.	n.a.	standard	standard
Wheel lift	option	option	option	standard

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE) Phone: +39 0522 733-411 · Fax: +39 0522 733-479 · www.hofmann-

Snap-on Equipment Austria GmbH · Hauptstrasse 24/Top 14 · A-2880 St. Corona/Wechsel (RE) Phone: +43 1 865 97 84 · Fax: +43 1 865 97 84 29 · www.hofmann-equipment.com

Snap-on Equipment France · ZA du Vert Galant · 15, rue de la Guivernone BP 97175 :-Ouen-l'Aumône · 95056 Cergy-Pontoise CEDEX e: +33 134 48 58-78 · Fax: +33 134 48 58-70 · www.hofmann-equipment.com

on Equipment GmbH · Konrad-Zuse-Straße 1 · 84579 Unterneukirchen 2: +49 8634 622-0 · Fax: +49 8634 5501 · www.hofmann-equipment.com

....y Snap-on Equipment s.r.l. • Via Prov. Carpi, 33 • 42015 Correggio (RE) Phone: +39 0522 733-411 • Fax: +39 0522 733-410 • www.hofmann-equipment.com

United Kingdom Snap-on Equipment Ltd. • Unit 17 Denney Road, King's Lynn • Norfolk PE30 4HG Phone: +44 118 929-6811 • Fax: +44 118 966-4369 • www.hofmann-equipment.com

