

MONO CLIMA

- 220V 50Hz
- BIPOWER

DISPONIBILE IN
VERSIONI:
AVAILABLE IN VERSIONS:

**220V 50Hz
BIPOWER**



IT

**Stazione aria condizionata monogas R134a
carrellata. Per uso esterno (agricoltura,
macchine movimento terra, etc.) con
alimentazione 220V 50Hz oppure 12V DC (con
kit Bipower)**

- Compressore di recupero con separatore automatico dell'olio
- Pompa per vuoto da 3m³/h monostadio
- Cilindro di carica da 4,4kg con resistenza di riscaldamento e valvola di sicurezza
- Gruppo manometrico a 4 vie con manometri \varnothing 80 Pulse free
- Iniettore per olio fresco
- Capacità di recupero: 400gr/min
- Tubi L=2mt
- Alimentazione: 220 V 50 Hz/12 V DC
- Dimensioni: 50x40x115H cm
- Peso 50 Kg



Versione / Version 12V DC-220V AC
Cod. 01.009.02

EN

**Manual a/c station for R134a for service on
agricultural machines, earth-moving machines
and boats with power supply 220V 50Hz or 12V
DC (with Bipower kit)**

- Compressor for recovery with automatic oil recovery system
- 3m³/h single/stage vacuum pump
- 4.4kg charge cylinder with heating resistance and safety valve
- Fresh oil injector
- 4-way manometric group with pressure gauges \varnothing 80mm Pulse free
- Recovery capacity: 400gr/min
- Hose L=2mt
- Power supply: 220 V 50 Hz/12 V DC
- Dimensions: 50x40x115H cm
- Weight: 50 Kg

MONOCLIMA 220V 50Hz

COD. 01.009.01

€ 2.200,00

MONOCLIMA BIPOWER 12V DC-220V AC

COD. 01.009.02

€ 2.600,00

